

**MST REMOTE STROBE**  
**P.N. 8008503**  
**(SUPPLIED WITH 20 F T. CORD/PLUG EXTENSION)**

**OPERATING VOLTAGE** ..... **12 VDC**

**POWER CONSUMPTION** ..... **140 mA**

**FLASH RATE** ..... **60 PER MINUTE**

**CANDLE POWER** ..... **150,000 CP**

**OPERATING LIFE** ..... **800 HOURS**

**STROBE BASE MATERIAL** ..... **UL-94 FLAME RETARDANT PLASTIC**

**STROBE LENS MATERIAL** ..... **CLEAR POLYCARBONATE**

**POWER CORD** ..... **20 FT., 18 AWG/2C, SPT-1, VW-1, 221° F (105° C)**

**OPTIONAL** ..... **UP TO 250 FT. OF CORD CAN BE SUPPLIED**

**NOTE: THE MST MONITOR REQUIRES OPTIONAL POWER SOURCE HOOK-UP (i.e. P.N. 80247 120 VAC ADAPTER OR P.N. 80123 12 VDC ADAPTER) TO ENERGIZE STROBE EFFECTIVELY. THE STANDARD POWER SOURCE (i.e. (2) 9-VOLT TRANSISTOR BATTERIES) WILL NOT ENERGIZE STROBE).**

**NOTE: MST® RESERVES THE RIGHT TO CHANGE OR MODIFY SPECIFICATIONS AND/OR PRODUCTS.**

